



LW MEASUREMENTS LLC



Category	NTEP Certificate Number: 19-137			
Model	FBS-W/FB-W			
Model Suffix	500			
Casing	Stainless steel/cast steel			
Capacity	500lb			
2nd Capacity	No			
Resolution(lb)	0.1lb			
Resolution(kg)	0.05kg			
Resolution(oz)	2 oz			
Resolution				
Resolution				
No. of Display Divisions	5000			
No. of Internal Resolutions	2 m			
Accuracy	+/-2d			
Platter Size(inch)	16 x 20	18 x 18	18 x 24	24 x 24
Draft Shield	No			
Scale Dimensions(inch)	20 x 21 x 33	18 x 23 x 33	24 x 23 x 33	24 x 29 x 33
LCD Height(inch)	1.34			
Beeper	Yes			
Auto Backlight	Yes,Selectable			
Auto Shut Off	Yes,Selectable			
Auto Hold	No			
Unit Switching	kg, lb oz			
AD Processor	21 bit A/D			
AD Update Speed	7.5 Hz			
Settling Time	<2s			
Calibration Software	AnyCal			
No of Keys	7			
Memory	Zero			
Counting Function	Yes			
RS232C	Yes			
USB	Yes			
Battery	7.4V 2200mAh Rechargeable			
AC Adapter	Yes, 12VDC			
Shipping Weight(lb)	45	45	55	60
Pieces per master ctn	1	1	1	1
Units per pallet	22	22	15	13
Cabel Length (ft)	/			



NTEP Certificate Number: 19-137

FBS-C/FB-C

500

Stainless steel/cast steel

5001b

No

0.1lb

0.05kg

2 oz

5000

2 m

+/-2d

16 x 20

18 x 18

18 x 24

24 x 24

No

20 x 21 x 33

18 x 23 x 33

24 x 23 x 33

24 x 29 x 33

1.34

Yes

Yes,Selectable

Yes,Selectable

No

kg, lb oz

21 bit A/D

7.5 Hz

<2s

AnyCal

18

Zero

Yes

Yes

Yes

7.4V 2200mAh Rechargeable

Yes, 12VDC

45

45

55

60

1

1

1

1

22

22

15

13

/



FBX-W	FBX-C
wash down	
Stainless steel	
/	/
No	
/	/
/	/
/	/
/	/
/	/
No	
9.9 x 6.8 x 5.1	
1.34	
Yes	
Yes,Selectable	
Yes,Selectable	
No	
kg, lb oz	
21 bit A/D	
7.5 Hz	
<2s	
AnyCal	
7	18
Zero	
Yes	
Yes	
Yes	
7.4V 2200mAh Rechargeable	
Yes, 12VDC	
4.5	4.5
6	6
144	144
6	